



OSBORNE®

Stainless Steel Rectangular Feeders

All Osborne rectangular feeder models are constructed with heavy 16 gauge 304 stainless steel or equivalent. Solid welded construction ensures durable, long-lasting performance, and roll-hemmed edges provide extra strength with no sharp edges. Use the simple adjustments to promote optimum feed efficiency. Multiple holes and knockouts allow for mounting the feeders in multiple applications.



Pictured above: **FF-CSW42-203**
42" Wet/Dry Wean-to-Finish Feeder



Solid divider panels with pre-drilled holes allow for splitting the feeder among sort and grower pens.



Simple adjustment system keeps animals from resetting the feeder.



Stainless steel nipple bar is easy to remove.

OSBORNE WEAN-TO-FINISH RECTANGULAR FEEDERS

Catalog Number	Style	Trough Spaces	Trough Space Width (in cm)	Trough Space Height (in cm)	Feed Capacity* (lbs kg)	Length (in cm)	Width (in cm)	Height (in cm)	Tube Brackets	Hog Capacity*
FF-WF42-223	Standard Double-sided	3	14 35.5	4.5 11	388 176	42 107	25 64	34 86	1	42
FF-WF60-224	Standard Double-sided	4	15 38	4.5 11	554 251	60 152	25 64	34 86	2	60
FF-CSW42-203	Wet/Dry Double-sided Stainless Steel Nipple Waterers	3	14 35.5	4.5 11	229 104	42 107	22 56	31 79	1	42
FF-CSW60-204	Wet/Dry Double-sided Stainless Steel Nipple Waterers	4	15 38	4.5 11	328 149	60 152	22 56	31 79	2	60

* Approximate feed capacity based on feed density of 42 lbs. per cubic foot.

* Hog capacity based 1 pig per 2 in. of trough length.

Call us today to learn more about our Feeders.
Osborne Feeders are one key to opening our
Single Source Swine Solutions™.



Single Source
SWINE SOLUTIONS™

Osborne Customer Service

Toll Free: 1-800-255-0316 · International: +1-785-346-2192

E-mail: sales@osborne-ind.com

Web: www.osbornelivestockequipment.com

© 2012-2016 Osborne Industries, Inc.